



REGELTEX INSULATING GLOVES (For Electrical Works)



Class	Length Available	Categories	Thickness in mm*	Size Available	Colour of Packaging
00	28/36 cm	AZC	0.5	8-9-10-11	Beige
0	36/41 cm	AZC	1.0	8-9-10-11	Red
1	36/41 cm	AZC	1.5	8-9-10-11	White
2	36/41 cm	RC	2.3	8-9-10-11	Yellow
3	36/41 cm	RC	2.9	8-9-10-11	Green
4	41 cm	RC	3.6	9-10-11	Orange

\* Obtaining the category authorises an additional thickness of 0.6 mm

Signification of category letters :

- A : Acid
- Z : Ozone
- H : Oil
- C : Very low temperatures
- R : A+Z+H

Electrical requirements (routine test and sampling test in alternating current)

Class	Max Operating Voltage (volts)	Proof Test Voltage (volts)	Whitstand Voltage (volts)
00	500	2500	5000
0	1000	5000	10000
1	7500	10000	20000
2	17000	20000	30000
3	26500	30000	40000
4	36000	40000	50000

Order No.	Type
307010710001	RG - 5K - CLASS00 - 36 - 10
307010710002	RG - 10K - CLASS0 - 36 - 10
307010710003	RG - 20K - CLASS1 - 36 - 10
307010710004	RG - 30K - CLASS2 - 36 - 10

